

## WALL PATCH

5

### CLAIMS

#### What is Claimed is:

- 10 1. A wall patch, comprising:  
a substantially planar body;  
an adhesive located on a lower surface of the body; and  
a ready-to-paint upper surface of the body.
- 15 2. A wall patch according to claim 1, wherein the body further comprises a perimeter having  
a feathered edge.
3. A wall patch according to claim 1, wherein the ready-to-paint outward surface comprises  
a texture.
- 20 4. A wall patch according to claim 1, wherein the body is formed from a tear-resistant  
material.
5. A wall patch according to claim 1, wherein the body is formed of biaxially oriented three-  
25 ply polypropylene film.
6. A wall repair system comprising;  
a self-adhesive wall patch having a ready-to-paint outward surface; and  
a center reinforcement.
- 30 7. A wall repair system according to claim 6, wherein the wall patch is formed from a  
biaxially oriented three-ply polypropylene film.

8. A wall repair system according to claim 6, wherein the center reinforcement is a rigid metal or plastic wall patch.

9. A wall repair system according to claim 6, wherein the center reinforcement is a smooth, self-adhesive plastic or fibered-paper wall patch.

10. A method for repairing a hole in a wall, comprising:  
selecting a wall patch having an outward surface adapted to be directly paintable;  
applying the wall patch over a hole; and  
painting directly over the wall patch.

11. A method for repairing a hole in a wall according to claim 10, further comprising applying a center reinforcement over the hole before applying the self-adhesive wall patch.

12. A method for repairing a hole in a wall according to claim 11, wherein the center reinforcement is a rigid wall patch and wherein applying a center reinforcement comprises:  
removing an upper surface portion of the wall around the hole in a shape corresponding to a shape of the rigid wall patch to a depth approximately equal to the thickness of the rigid wall patch to form a recessed area; and  
placing the rigid wall patch within the recessed area.

13. A method for repairing a hole in a wall according to claim 11, wherein the center reinforcement is formed from a fibered paper or plastic material.

14. A method for repairing a hole in a wall according to claim 10, wherein the wall patch is formed from a biaxially oriented three-ply polypropylene film

15. A method for repairing a hole in a wall, according to claim 10, wherein the wall patch comprises a pre-textured rigid wall patch, and wherein applying a wall patch over the hole comprises:

removing an upper surface of the wall around the hole in a shape corresponding to the shape of the rigid wall patch to a depth approximately equal to the thickness of the rigid wall patch to form a recessed area; and

placing the rigid wall patch into the recessed area.

5

16. A method for repairing a hole in a wall, according to claim 15, wherein the rigid wall patch has a substantially rectangular shape having four corners and wherein at least one of the corners is directed inwardly in the direction of a bottom surface thereof, the method further comprising:

10 forcing the inwardly directed corner of the rigid wall patch into the wall to secure the rigid wall patch over the hole; and

tracing an outline of the rigid wall patch along the wall to define the shape on the upper surface of the wall for removal.

15 17. A method for repairing a hole in a wall, according to claim 16, further comprising:  
selecting a wall patch strip having an upper surface adapted to be directly paintable;  
placing the wall patch strip over a crack between the rigid wall patch and the wall surface.

18. A wall patch for repairing a hole or a crack in a wall, comprising:  
20 a substantially planar, flexible body;  
an adhesive located on a lower surface of the body; and  
a ready-to-paint upper surface located on the body.

19. A wall patch according to claim 18, wherein the ready-to-paint upper surface of the body  
25 is pre-textured and wherein one or more edges of the body are feathered to allow the body to more readily mate with a textured wall surface.

20. A wall patch according to claim 18, wherein the body is formed from a biaxially oriented, three-ply, polyethylene film.

30